## **Declaration of Performance**



801 1 Product code

2 Product type All Besblock pumice solid blocks of 215mm high

3 Intended use In walls, columns and partitions

4 Company name & Besblock Limited contact address Halesfield 21

Telford

Shropshire TF7 4NF United Kingdom.

5 Name & contact address of

responsible person

4

NA

6 System of Assessment &

Verification of Constancy of

Performance

7 Harmonised standard BSEN771-3

8 European Technical Assessment n/a

9 **Declared Performance:** 

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	440mm	
	Width	75mm 90mm 100mm 115mm 140mm 150mm 190mm 200mm 215mm	
	Height	215mm	EN 771-3: 2011
	Tolerance	D1	
Configuration Compressive strength	Shape & features	NPD	
	Group according EN 1996-1-1 (EC6)	Group 1 (Solid)	
	Mean Compressive strength	7.3 - 10.4 N/mm2(Unit Strength)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability		<0.6mm/m	
Bond strength	Shear bond strength	0.15N/mm² (tabulated Value)	
	Flexural bond strength	NPD	
Reaction to fire		A1	
Water absorption		NPD	
Water vapour permeability		5/15 (Tabulated value)	
Direct airborne sound insulation	Gross density	1350kg/m3	
(in end conditions )/ [Density and configuration]	Configuration; dimensions and tolerances	Group 1 ( Solid)	

Effective lambda value / [Density and configuration] (for units intended to be used	$\lambda$ 0.29 W/(mK) <sub>10, dry mat</sub>	EN 771-3: 2011
in elements subject to thermal isulation reguirements)	1350kg/m3	
Durability against freeze/thaw	Pass	
Dangerous substances	NPD	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Robin Huxley, Director

Signature:

Valid From: 01/06/2013