

Declaration of Performance

1 2	Product code Product type	305 Besblock Solite solid blocks (440 x 215 x 100mm)
3	Intended use	In walls, columns and partitions
4	Company name & contact address	Besblock Limited Halesfield 21 Telford Shropshire TF7 4NF United Kingdom.
5	Name & contact address of responsible person	NA
6	System of Assessment & Verification of Constancy of Performance	4
7	Harmonised standard	BSEN771-3

n/a

- 8 European Technical Assessment
- 9 Declared Performance:

Essential Cha	racteristics	Performance	Harmonised Technical
			Specification
	Length	440mm	
Dimensions	Width	100mm	
	Height	215mm	
	Tolerance	D1	
	Shape & features	NPD	
Configuration	Group according EN 1996-1-1 (EC6)	Group 1 (Solid)	EN 771-3: 2011
Compressive strength	Mean Compressive strength	3.6N/mm2 (Unit Strength)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability		<0.7mm/m	
Bond strength	Shear bond strength	0.15N/mm ² (tabulated Value)	
	Flexural bond strength	NPD	
Reaction to fire		A1	
Water absorption		NPD	
Water vapour permeability		5/15 (Tabulated value)	
Direct airborne sound insulation (5)	Gross density	1057kg/m3	
(in end conditions)/ [Density and configuration]	Configuration; dimensions and tolerances	Group 1 (Solid)	

Effective lambda value / [Density and configuration] (for units intended to be used	λ 0.26 W/(mK) $_{\rm 10,drymat}$	
in elements subject to thermal isulation reguirements)	1057kg/m3	
Durability against freeze/thaw	Not to be used exposed	EN 771-3: 2011
Dangerous substances	NPD	-

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer

identified in point 4.

Signed for and on behalf of the manufacturer by:

Name:

Robin Huxley, Director

RoomArten

Signature: Valid From:

01/06/2013