

Declaration of Performance

1 2 3	Product code Product type Intended use	191 Millennium Facing Masonry (140mm Cellular block) In walls, columns and partitions
э	Intended use	in wais, columns and partitions
4	Company name & contact address	Besblock Limited Halesfield 21 Telford Shropshire TF7 4NF United Kingdom.
5	Name & contact address of responsible person	NA
6	System of Assessment & Verification of Constancy of Performance	4
7	Harmonised standard	BSEN771-3

n/a

- 8 European Technical Assessment
- 9 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
	Length	440mm	
Dimensions	Width	140mm	
	Height	215mm	
	Tolerance	D1	
	Shape & features	NPD	
Configuration	Group according EN 1996-1-1 (EC6)	Group 2 (Cellular > 25% void)	EN 771-3: 2011
Compressive strength	Mean Compressive strength	3.6 - 10.4N/mm ² (Unit Strength)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability		<0.4mm/m	
Bond strength	Shear bond strength	0.15N/mm ² (tabulated Value)	
	Flexural bond strength	NPD	
Reaction to fire		A1	
Water absorption		0.3 (g/m2s)	
Water vapour permeability		50/150 (Tabulated value)	
Direct airborne sound insulation	Gross density	1574kg/m3	
(in end conditions)/ [Density and configuration]	Configuration; dimensions and tolerances	Group 2 (Cellular > 25% void)	

Effective lambda value / [Density and configuration] (for units intended to be used	λ 0.91 W/(mK) $_{\rm 10,drymat}$	
in elements subject to thermal isulation reguirements)	1574kg/m3	
Durability against freeze/thaw	Pass	EN 771-3: 2011
balability against heerey that	r 655	
Dangerous substances	NPD	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer

identified in point 4.

Signed for and on behalf of the manufacturer by:

Name:

Robin Huxley, Director

RoomArten

Signature: Valid From:

01/06/2013