## **Declaration of Performance**

OCK BUILDIN
BLOCK BUILDIN
BLOCK BUILDIN
COKS BESBL

OCKS BESBLOCK BUILDIN
BESBLOCK BUILDIN
BESBLOCK BUILDIN
BESBLOCK BUILDIN

1 Product code 74

2 **Product type** Bescrete Cellular Super 15: (440 x 140x 215mm)

3 Intended use In walls, columns and partitions

4 Company name & Besblock Limited contact address Halesfield 21

Telford

Shropshire TF7 4NF United Kingdom.

5 Name & contact address of

responsible person

\_

NA

6 System of Assessment &

Verification of Constancy of

4

Performance
7 Harmonised standard

BSEN771-3

8 European Technical Assessment

n/a

## 9 **Declared Performance:**

Declared Periorillance.		B. (	11
Essential Characteristics		Performance	Harmonised Technical
			Specification
Dimensions	Length	440mm	
	Width	140mm	
	Height	215mm	
	Tolerance	D1	
	Shape & features	NPD	
Configuration	Group according EN 1996-1-1 (EC6)	Group 1 (Cellular < 25% void)	EN 771-3: 2011
Compressive strength	Mean Compressive strength	3.6 - 10.4N/mm <sup>2</sup> (Unit Strength)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability		<0.7mm/m	
Bond strength	Shear bond strength	0.15N/mm² (tabulated Value)	
	Flexural bond strength	NPD	
Reaction to fire		A1	
Water absorption		NPD	
Water vapour permeability		5/15 (Tabulated value)	
Direct airborne sound insulation	Gross density	1632kg/m3	
(in end conditions )/ [Density and configuration]	Configuration; dimensions and tolerances	Group 1 ( Cellular < 25% void)	

Effective lambda value / [Density and configuration] (for units intended to be used	$\lambda$ 0.641 W/(mK) <sub>10, dry mat</sub>	
in elements subject to thermal isulation reguirements)	1632kg/m3	
	Group (Cellular < 25% void)	EN 771-3: 2011
Durability against freeze/thaw	Pass	
Dangerous substances	NPD	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Robin Huxley, Director

Signature:

Valid From: 01/06/2013