## **Declaration of Performance**

OCK BUILDING BLOCK BUILDING BUILDING BLOCK BUILDING BUILDING BLOCK BUILDING BUILD

1 Product code 13

2 **Product type** Insulite 200mm Hollow: (440 x 200 x 215)

3 Intended use In walls, columns and partitions

4 Company name & Besblock Limited contact address Halesfield 21

Telford

NA

4

Shropshire TF7 4NF United Kingdom.

5 Name & contact address of

responsible person

6 System of Assessment &

Verification of Constancy of

Performance

7 Harmonised standard BSEN771-3

8 European Technical Assessment n/a

9 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
	Length	440mm	
Dimensions	Width	200mm	
	Height	215mm	
	Tolerance	D1	
	Shape & features	NPD	EN 771-3: 2011
Configuration	Group according EN 1996-1-1 (EC6)	Group 2 (Hollow > 25% void)	
Compressive strength	Mean Compressive strength	3.6 - 7.3N/mm <sup>2</sup> (Unit Strength)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability		<0.6mm/m	
Bond strength	Shear bond strength	0.15N/mm² (tabulated Value)	
	Flexural bond strength	NPD	
Reaction to fire		A1	
Water absorption		NPD	
Water vapour permeability		5/15 (Tabulated value)	
Direct airborne sound insulation (in end conditions )/ [Density and configuration]	Gross density	952kg/m3	
	Configuration; dimensions and tolerances	Group 2 ( Hollow > 25% void)	

Effective lambda value / [Density and configuration] (for units intended to be used	$\lambda$ 0.523 W/(mK) <sub>10, dry mat</sub>	
in elements subject to thermal isulation reguirements)	952kg/m3	
	Group 2 (Hollow > 25% void)	EN 771-3: 2011
Durability against freeze/thaw	Not to be used exposed if < 7.3N/mm2	
Dangerous substances	NPD	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Robin Huxley, Director

Signature:

Valid From: 01/06/2013